

R2001 GENERATOR

Forward Power Output	2000 Watts
Frequency (specify when ordering)	1.7-2.1 MHz, 13.56MHz
Forward Power Accuracy	+/- 2%
Harmonics	-50 dBc
Input Power	200-240VAC Single Phase or 3 Phase, 47-63 Hz or 380-415V 3 Phase, 47-63 Hz (specify when ordering)
Output Connector	Type "N", "HN", or 7/16 DIN Female (specify when ordering)
Interface Connectors	Serial: DB-9 Female; Analog: DB-25 Female
Pulsing	0 - 100 % Duty Cycle, 50 μs minimum pulse width
Cooling	Water Cooled, 2.0 GPM @ 40°C Water IN/OUT Connection: 3/8" NPT Female
Ventilation	Forced Air, 150 CFM (70.79 L/s)
CEX Input - (BNC)	5V Peak-to-Peak, nominal sine wave
CEX Output - (BNC)	6V Peak-to-Peak, nominal sine wave
SEMI - Third Party	SEMI S2, SEMI S8
EMC & Safety - Third Party	CE Mark
Dimensions - (H,W,D)	7.00" x 19.00" x 22.75" (17.7 x 48.2 x 57.7 cm)
Weight	55 Lbs (24.9 Kg)

